


PB-48-200H



• LITHIUM BATTERY

Strong Advantages

- 6 Years Warranty
- Replacement of lead-acid battery
- Lighter weight and easier to handle
- Lithium iron phosphate is more stable
- Maximum service life of over 6000 cycles
- Long-lasting modular construction
- Screw opening, perfect crafted internal structure design

• ELECTRIC HEATING FILM

- Some of the Perfektium lithium batteries are equipped with heating films. You can use the battery in temperatures as low as -35 degrees Celsius when acting the heating films
- The heating film is an IP material and the heating effect is even
- The heating films do not consume any power from the battery itself

• BMS

Battery Management System

The BMS monitors and controls the individual cells of each battery and protects them from damage, such as overload

• BLUETOOTH 4.0 INTEGRATED Multiple Battery Monitoring Function

Perfektium Pro APP can monitor up to 8 batteries at the same time. The SOC, voltage, current, temperature, available time of the batteries can be detective.





Specification

Items	Characteristics
Model	51.2V 200Ah/10240Wh
Replaces Gel-AGM battery	51.2V 400Ah
Cell type	Prismatic cell
Dimension with terminals (L x W x H)	570*380*230mm
Weight (No Accessories)	76,7Kg
Cycle Life	>6000@80%D.o.D
Internal Resistance	$\leq 14\text{ m}\Omega$
Recommended Charge Voltage	58.4V
Float Charge Voltage (For standby use)	55.2 $\pm$ 0.8V
Recommended Charge Current	60A
Max Charge Current	100A
Continuous Discharge Current	250A
Peak Discharge Cut-Off Current	600A (200~500ms)
Operating Voltage Range	40 - 58.4V
End of Discharge Voltage Range	40 - 44.8V
Terminal Type	M8
Ingress Protection Code	IP64
Charge Temperature	0~50°C
Discharge Temperature	-20~75°C
Storage Temperature	-5~35°C
Heater Operating Temperature	-35~5°C
Storage Condition	Charging the battery every 3 months
Series & Parallel Availability	Only 4 parallel at most
Certifications	CE/UL/UN38.3/MSDS/ROHS/UN 3480/CLASS9/ECE R10